

SPECIFICATIONS

Model Name		INDOOR UNIT (IDU)	GTKU50UV16VF	
		OUTDOOR UNIT (ODU)	RKUG50UV16VF	
Star Rating *			5 Star	
Rated Power Supply (Phase/ Frequency/Voltage)			1Ø/50Hz/230v (220..240V)	
Power Supply Intake			Outdoor unit	
Rated Cooling Capacity Full/Half (Min~Max.)		Kw	5/2.5(1.5.5.6)	
		Btu/h	17100/4550(5100.19100)	
Rated Power Consumption Full/Half (Min~Max)	Cooling	W	1310/420 (250..1600)	
Rated Annual Power Consumption		Kwh	744.5	
Rated Iseer		wh/Wh	5.2	
Voltage Range (Stablizer Inside)	Cooling	V	130.285	
Operating Current	Cooling	A	5.84	
INDOOR UNIT (IDU)	Panel Colour		White	
	Idu Dimension (Hxwxd)		mm	
	Package Dimension (Hxwxd)			298x885x229
	Idu Net Weight (Gross Weight)		kg	10.5 (13.5)
	Airflow Rate	Cooling	Feet3/min (cfm)	593
			m3/min (cmm)	16.8
	Operating Sound H/M/M L/L/S L	Cooling	Dba	48/46/43/41/38/32
OUTDOOR UNIT (ODU)	Odu Dimension (Hxwxd)		mm	
	Package Dimension (Hxwxd)		595 x 845 x 300	
	Odu Net Weight (Gross Weight)		kg	680 x 1035 x 410 30.5(37.5)
	Compressor Type		Swing Compressor	
	Refrigerant		R-32	
Breaker Size		A	20	
Piping Length	Change Less	m	10	
	Max.Length		20	
	Max. Height		16	
Piping Connection	Gas/Liquid	mm(Inch)	Ø-12.75/Ø6.4(1/2"/1/4")	
Operating Ambient Temperature Range	Cooling (Min ~ Max)	°C DB	20.54	